

EP29714 ④

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 045 608 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

18.10.2000 Bulletin 2000/42

(51) Int. Cl.⁷: H04Q 7/38

(21) Application number: 98107590.6

(22) Date of filing: 25.04.1998

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE

Designated Extension States:

AL LT LV MK RO SI

(71) Applicant: ROBERT BOSCH GMBH

70442 Stuttgart (DE)


(72) Inventor: Bisgaard, Peter

9440 Aabybro (DK)

(54) **A method for network selection for mobile digital communication systems**

(57) The invention provides a method for network selection for a mobile digital communication system having a plurality of mobile stations being adapted to communicate over a selected one of a plurality of networks originating from different countries, said networks (A, B, C) providing the mobiles with respective identifications including an associated country identification code, comprising the steps of entering and storing the country identification code of a desired country (L1) from which a selectable network (A, B) must originate in a mobile; determining the availability of any network having said entered country identification code from said mobile; and if at least one network (A, B) of the desired country is available, selecting said one network by said mobile, otherwise continuing the step of determining.

FIG. 1



EP 1 045 608 A1

Description

BACKGROUND OF THE INVENTION

[0001] The present invention relates to a method for network selection for a mobile digital communication system having a plurality of mobile stations being adapted to communicate over a selected one of a plurality of networks originating from different countries, said networks providing the mobiles with respective identifications including an associated country identification code.

[0002] Although applicable to any mobile digital communication system, the present invention and its underlying problems will be discussed with particular reference to GSM mobile systems.

[0003] In current standard GSM mobile communication systems, there are two concepts for network selection which all GSM mobiles must support, and it is very likely that UMTS (Universal Mobile Telecommunication System) will inherit these concepts from GSM when UMTS standard is made. All GSM mobiles must provide the user with an automatic and a manual selection mode.

[0004] In the automatic selection mode, the mobile station selects the network to enter service on automatically, i.e. by means of a dedicated intelligent control circuit. The procedure performed by this circuit is the following. When the mobile is switched on, it will search for the network it was on service at the time it was switched off. If this network is available, said network will be selected. If this network is not or no longer available, the mobile will automatically choose among other available and preferred networks.

[0005] The search and judgement of availability usually involves the measurement of the electric field strength of the networks wherefrom radio signals may be received. Typically all networks whose field strength lies above a certain threshold will be entered into a list of available networks, either ordered by signal strength or by predetermined priority or preference rules. In other words, the user has a possibility to give priority to the networks he prefers by editing a list of preference which is stored on the SIM. This list is used by the mobile to sort the list of available networks such that registration is attempted on the networks in the order they are listed in the list of preference.

[0006] In the manual selection mode, the mobile station selects the network to enter service on by manual input of the user. By means of the dedicated intelligent control circuit, the mobile provides the user with a list of all currently available networks, and the user must then choose one of these, f.e. by pushing a select button. The mobile will then stay on service on this network, and if coverage is lost, the user is provided with a new list of all networks available at that time and site.

[0007] Usually a mobile is subscribed to a single network called its home network. When a mobile enters

service on another network which it is not subscribed to, this is called roaming. The roaming concept is typically divided into two cases, the national roaming and the international roaming, depending on whether the network into which the mobile logs in belongs to the same country as its home network or not.

[0008] Instead of having to provide coverage in the complete country, two or more operators can cooperate by making a national roaming agreement. This means that subscribers from one network may obtain service by using another network in areas where their home network does not provide coverage. Hence, a new operator on the market with very little coverage is able to obtain practically full coverage from the day he launches his operation by having such roaming agreement(s).

[0009] In case a mobile which is subscribed a new operator is in automatic selection mode, it will automatically enter service on another network when it moves out of coverage from its home network.

[0010] Usually, mobiles using national roaming have implemented a timer which effects that the mobile, if it has lost its home network and is in service on a foreign network, will periodically search for its home network and return to it in case it is available again.

[0011] Such a timer is not used in the international roaming case as this will reduce the stand-by time, as the search for the home network consumes energy and it is improbable that in a foreign country the home network will be found after a short time.

[0012] The use of the automatic and manual selection modes in GSM is described thoroughly in GSM 02.11, ETS 300 507, and GSM 03.22, ETS 300 535.

[0013] The two known selection modes involve the so-called border area problem which can occur in border areas between two or more adjacent countries, as described in GSM MoU TWG Technical Note 3, version 4.0, Network Selection in border areas. As radio waves aren't stopped by national country borders, there are areas in which a mobile station is able to enter normal service operation on networks from more than one country. From the user's point of view, entering service on a network of a foreign country is problematic, as calling with the mobile station can be much more expensive than under normal conditions, i.e. under service on national networks.

[0014] In the following, the particular problems arising in the two above described known selection modes will be discussed with reference to Fig. 1 which is a schematic illustration of exemplary coverage conditions at a country border to discuss the problems with the prior art.

[0015] In Fig. 1 reference sign BL denotes a borderline between the two countries L1 and L2. In the shown area of country L1, two national networks A and B are available in respective coverage regions indicated by first circle sections of circles A and B. Moreover, in the shown area of country L1, one foreign network C is available in a coverage region indicated by a first circle

section of circle C.

[0016] On the other hand, in the shown area of country L2, the national network C is available in a coverage region indicated by the complementary second circle section of circle C; and in the shown area of country L2, the two foreign networks A and B are available in respective coverage regions indicated by complementary second circle sections of circles A and B.

[0017] The dashed line R denotes a route of a mobile through the shown area of country L1, i.e. its home country, in the vicinity of the borderline BL, and M1 to M5 denote five special mobile positions passed by the mobile one after another.

[0018] In automatic mode, there is the possibility that the mobile will roam onto a foreign network in the border area. This happens if the mobile temporarily loses coverage from its current national network (home network or national roaming network). In Fig. 1 such a situation would be encountered at mobile position M3 when coming from M1 via M2, namely at this point the mobile would enter service on foreign network C. Since no timer is implemented for this situation of international roaming, the mobile will stay in service on foreign network C until it loses connection therewith, i.e. at mobile position M5 in Fig. 1. On the other hand, the international roaming would only be necessary until the mobile enters the coverage of network B shortly after mobile position M3.

[0019] The problem is that the price paid for making and receiving calls is considerably higher in foreign network C. In case of an incoming call, the calling party only pays the price for a regular national call, however, the mobile subscriber pays for routing the call from its home country, here L1, to the foreign network C of country L2. In case the mobile subscriber initiates a call while internationally roaming on foreign network C, he won't only pay the price for a regular national call, but additionally pay the price for routing the call from the foreign country, here L2, to its home country L1. Thus, in both directions the price is considerably enhanced.

[0020] Due to the border area problem, mobile subscribers living in border areas are currently better off using the manual selection mode, where the mobile will only search for available networks, however, the selection itself is carried out manually by the user. Here the problem is that the manual selection mode prevents national roaming from occurring automatically, which means that the user has to bother all the time whether the mobile is still on service or not. Manual selection is therefore annoying to a user who often needs national roaming.

[0021] In summary, the state of the art in form of manual and automatic selection mode having a timer for national roaming but no timer for international roaming as discussed above does not provide any comfortable solution to the border area problem.

[0022] The border area problem has been discussed for some time in ETSI. As a possible solution, it

has been suggested to implement a timer for international roaming as it is done in the case of national roaming. This suggestion, however, has so far been rejected in ETSI as on one hand it would reduce the stand-by time of the mobiles implementing such a feature as already mentioned above and on the other hand it would be an expensive solution for a problem which only occurs in border areas for a small percentage of the users.

[0023] Another suggestion has been to let the user make his own forbidden list, such that he could define which networks he does not want to receive service from. However, this solution is not satisfactory either, as the user would have to enable and disable such an exclusion when travelling (f.e. for holidays) into the country of the network he wishes to exclude when being at home. Moreover, the exclusion would have to be modified depending on at which border area the user is on tour and depending on the coverage density of national networks in this border area. Finally, the network providers do not like the idea that the user can prevent the mobile to access their networks in this manner.

SUMMARY OF THE INVENTION

[0024] The present invention provides a method as defined in independent claim 1. Preferred embodiments of the present invention are listed in the dependent claims.

[0025] The core idea of the present invention is to introduce a third mode of network selection which helps to avoid the problems cited above. In the third mode which is called country selection mode, the user must choose a country manually instead of a network. Thus, in country selection mode the mobile must only attempt to enter service on networks which belong to a specified country. Within that country the mobile works exactly in the same manner as in automatic mode.

[0026] Advantageously, by having the country selection mode, mobile users living in border areas can avoid undesired international roaming to networks of neighbour countries while still having the automatic national roaming capability. In particular, the country selection mode is very easy and inexpensive to implement in the existing concepts for cellular telephony. Namely, it is possible to provide the manual and automatic modes explained above and to modify the automatic mode such that it only attempts service on the networks having the entered and stored country identification code of the desired country.

[0027] According to a preferred embodiment, a priority order is assigned to the plurality of networks; and if more than one network of the desired country is available, the network is selected according to said priority order. The priority can be entered from outside and stored or can be internally determined, f.e. under consideration of the respective field strength values.

[0028] According to a further preferred embodiment,

ment, the available networks are determined and a corresponding list of the currently available countries is presented to the user who selects this new mode. This helps to inform the user about his choice of countries.

[0029] According to a further preferred embodiment, if the mobile is just switched on, the availability of a network it was on service at the time it was switched off is determined; if said network is available, said network is selected, and if not, the step of determining is continued.

[0030] According to a further preferred embodiment, if coverage of a formerly selected network is lost, the steps of the determination of the availability and the selection are repeated.

[0031] According to a further preferred embodiment, a manual mode is selectable wherein the mobile provides a list of all currently available networks, and one of these may be selected.

[0032] According to a further preferred embodiment, if coverage of a formerly selected network is lost, a new list of all networks available at that time and site is provided.

[0033] According to a further preferred embodiment, the mobile comprises a timer means which periodically initializes the step of determining the availability of the mobile's home network, if the entered country identification code is the home country identification code, and which is deactivated, if not. Thus, the national roaming concept will work in the same manner as it does in mobiles having the known manual and automatic selection modes.

[0034] According to a further preferred embodiment, a current selection mode, and preferably an input country identification code, is stored in a non-volatile memory and used again when the mobile is powered off and on again. This involves the advantage the mobile will stay in a selected mode until the mode is changed by the user.

BRIEF DESCRIPTION OF THE DRAWINGS

[0035] The present invention will become more fully understood by the following detailed description of a preferred embodiment thereof in conjunction with the accompanying drawing, in which Fig. 1 which is a schematic illustration of exemplary coverage conditions at a country border.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0036] The following embodiment is relatively easy to implement in an existing mobile. In principle, the mobile must simply perform as it does in the known automatic mode, however, the country identification code of a desired country from which a selectable network must originate has to be entered and stored in the mobile. When determining the availability of any net-

work having said entered country identification code from said mobile, a comparison must be made to compare the country identification code of the respective networks with the one designated by the user.

[0037] Thus, from the apparatus view, a control procedure has to be slightly modified and an extra storage area for the code of the desired country in the existing memory be provided.

[0038] Particularly, in GSM standard each network transmits a code comprising five digits, where the first three digits identify the country and the last two digits identify the network in this country. For instance, the Danish operator Tele Danmark Mobile has the code 238-02, where 238 stands for Denmark and 02 for the operator.

[0039] The mobile of this embodiment has three modes, namely the known automatic and manual selection modes explained above and the new country selection mode.

[0040] With reference to Fig. 1, when the user switches on the mobile at mobile position M1 and selects the new country selection mode, the mobile searches available networks and then presents a corresponding list of the currently available countries (only country L1 at position M1), instead of a list of networks as it does in the manual selection mode. Thereafter, it asks the user to input a desired country identification code, f.e. by displaying a corresponding message on its LCD display window.

[0041] After having received the user's input by means of the push button panel, the mobile stores the desired country identification code, here the country identification code of country L1.

[0042] Now the mobile starts determining the availability of any network having said entered country identification code from said mobile; and since network A of the desired country L1 is available at mobile position M1, said network A is selected by the mobile, which network A the mobile is subscribed to.

[0043] When passing position M2, nothing happens, because network A is still available. At position M3, the coverage of network A is lost, and in principle service on network C could be obtained. However, since the desired country is L1 and network C belongs to country L2, no service on network C will be attempted. Instead a message is displayed on the LCD display window saying "SEARCHING NETWORK" or "NO SERVICE AVAILABLE".

[0044] At position M4, the mobile is again in service on network B which has the desired country identification code, however, is not its home network.

[0045] Thus, at position M5, the timer means initializes the step of determining the availability of the mobile's home network A, however, the determination is negative and the service on network B is kept. This is periodically repeated until a registration on network A is possible again.

[0046] Although the present invention has been

described with respect to a preferred embodiment thereof, it should be understood that many modifications can be performed without departing from the scope of the invention as defined by the appended claims.

[0047] Although in the described embodiment a single country identification code of a desired country from which a selectable network must originate was entered and stored, the mobiles could be designed such that there is the possibility of entering and storing the country identification codes of a plurality of desired countries from which a selectable network must originate.

[0048] Simultaneously an assignment of a priority order to the plurality of countries could be made. If at least one network of the desired countries is available, there would be a selection of said one network according to said priority order, otherwise the step of determining the availability would be continued.

LIST OF REFERENCE SIGNS:	
L1, L2	countries
A, B	networks of country L1
C	network of country L2
BL	borderline
M1 - M5	mobile positions
R	route of mobile

Claims

1. A method for network selection for a mobile digital communication system having a plurality of mobile stations being adapted to communicate over a selected one of a plurality of networks originating from different countries, said networks (A, B, C) providing the mobiles with respective identifications including an associated country identification code, comprising the steps of:

a) entering and storing the country identification code of a desired country (L1) from which a selectable network (A, B) must originate in a mobile;

b) determining the availability of any network having said entered country identification code from said mobile; and

c) if at least one network (A, B) of the desired country is available, selecting said one network by said mobile, and if not, continuing the step of determining.

2. A method according to claim 1, comprising the steps of assigning a priority order to the plurality of networks (A, B, C); and if more than one network (A, B) of the desired country is available, selecting the network according to said priority order.

3. A method according to claim 1 or 2, comprising the steps of determining the available networks and presenting a corresponding list of the currently available countries.

4. A method according to one of the preceeding claims, comprising the steps of:

if the mobile is just switched on, determining the availability of a network it was on service at the time it was switched off; if this network is available, selecting said network, otherwise continuing the step of determining.

5. The method according to claim 1, wherein if coverage of a formerly selected network is lost, steps b) and c) are repeated.

6. The method according to one of the preceeding claims, comprising the steps of:


selecting a manual mode wherein the mobile provides a list of all currently available networks, and one of these is selectable.

7. The method according to claim 6, wherein if coverage of a formerly selected network is lost, the a new list of all networks available at that time and site is provided.

8. The method according to one of the preceeding claims, wherein the mobiles comprise a timer means which periodically initializes the step of determining the availability of the mobile's home network, if the entered country identification code is the home country identification code, and which is deactivated, if not.

9. The method according to one of the preceeding claims, wherein a current selection mode, and preferably an input country identification code, is stored in a non-volatile memory and used again when the mobile is powered off and on again.

FIG. 1





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 10 7590

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	MOULY M ET AL: "PAGING AND LOCATION AREAS" 1 January 1993, GSM SYSTEM FOR MOBILE COMMUNICATIONS, PAGE(S) 442 - 458, MOULY M; PAUTET M-B XP002038439 * page 446, line 20 - page 452, line 30 *	1-9	H0407/38
A	EP 0 781 064 A (NOKIA MOBILE PHONES LTD) 25 June 1997 * column 9, line 8 - column 15, line 33 *	1-4,6,9	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			H04Q
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 30 September 1998	Examiner Maalismaa, J
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 10 92 (P/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 10 7590

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

30-09-1998

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0781064 A	25-06-1997	NONE	

EPO FORM P069

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☒ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.